

Datasheet

1.8" SATA SSD

3TG6-P series

- 2.5" SATA III solution for industrial field
- High IOPS
- iSMART disk health monitoring
- AES-256 encryption
- End to end data path protection
- iData Guard for abnormal power failure
- iCell technology for data protection (optional)
- DEVSLP supported



Introduction

Innodisk 1.8" SATA SSD 3TG6-P is SATA III 6Gb/s solid state disk, which delivers excellent performance, especially in random data transfer rate, and which offers reliability making it the ideal solution for a variety of applications, including embedded system, industrial computing, and enterprise field. 3TG6-P 1.8" SSD not only performs unmatched performance, but also designed with Innodisk owned technical knowhow to ensure the data integrity and highest levels of reliability.


1.8" SATA SSD

3TG6-P series

Drawing

Contact us for more information about the 1.8" SATA SSD 3TG6-P

Innodisk is a service-driven provider of industrial embedded flash and DRAM storage products and technologies, with a focus on the industrial/embedded, aerospace and defense, and cloud computing industries.



Headquarters (Taiwan)

5F., No.237, Sec. 1, Datong Rd.,
 Xizhi Dist., New Taipei City,
 Taiwan (R.O.C.)
 Tel: +886-2-77033000
 Email: sales@innodisk.com

Branch Offices:

USA
usasales@innodisk.com
 +1-510-770-9421
 Europe
eusales@innodisk.com
 +31-40-3045-400
 Japan
jpsales@innodisk.com
 +81-3-6667-0161
 China
sales_cn@innodisk.com
 +86-755-21673689
www.innodisk.com

© 2018 Innodisk Corporation.
 All right reserved. Specifications
 are subject to change without
 prior notice.

20181026

Specifications

Interface	SATA III
Flash Type	3D TLC
Capacity	128GB~1TB
Max. Channels	4
Sequential R/W (MB/sec, max.)*	530 / 460
4K Random (QD32) R/W (IOPS)*	TBD
Max. Power Consumption	TBD
Thermal Sensor	✓
External DRAM Buffer	✓
ATA Security	✓
S.M.A.R.T.	✓
Dimension (WxLxH)	54.0 X 78.5 X 5.00 mm
Environment	Vibration: 20G @7~2000Hz Shock: 1500G @ 0.5ms Storage Temperature: -55°C ~ +95°C MTBF: 3 million hours
*Performance based on CrystalDiskMark 3.03 with file size 1000MB	

Ordering Information

Operation Temp.	128GB	256GB	512GB	1TB
Standard Grade (0°C ~ +70°C)	DGS18-A28M71EC1QF	DGS18-B56M71EC1QF	DGS18-C12M71EC1QF	DGS18-01TM71EC1QF
Industrial Grade (-40°C ~ +85°C)	DGS18-A28M71EW1QF	DGS18-B56M71EW1QF	DGS18-C12M71EW1QF	DGS18-01TM71EW1QF