



Industrial 4U Rackmount Chassis with Front-Accessible USB Interface






Features

- Most cost-effective rackmount chassis.
- Supports 300/400/500 Watt ATX PFC PS/2 power supply.
- Easy-to-install front-accessible drive bays hold 3 x 5.25" and 2 x 3.5" drives (1 x front-accessible and 1 x internal)
- Designed to withstand environmental extremes, such as shock, vibration and high temperature
- Built in FSP400-60GHC SMPS

Specification

Components	Specification
Dimensions(WxDxH)	427mm x 450mm x 177mm, standard 19" rackmount chassis.
Materials	Quality fine 1.2mm SGCC steel.
Color	White
Drivers bay	4 x 3.5" HDD drive bays(compatible with 1 x 2.5" SSD).
CD-ROM	2 x front 5.25" optical drive slots (compatible with 1 x 3.5" hard drive or 1 x 2.5" SSD)
Cooling Fan	1 x 120mm fan on front.
PSU	FSP400-60GHC
M/B form factor	Support ATX 12" x 9.6" motherboard.
Epansion space	7 PCI expansion slots.
Connector	Two front accessible USB2.0 ports Optional USB 3.0.
System Control	POWER LED x 1, HDD LED x 1, RESET SW x 1, POWER SW x 1.
Application	Industrial PC , FACTORY AUTOMATION, CNC CONTROLLER, SECURITY MONITORING
Operating Temperature	0~50°C
Humidity	10 ~ 85% @ 40 °C, non-condensing





size up to ATX 12" x 9.6"

